



BELLINZONI S.R.L.

Revision nr. 8

Dated 24/02/2020

IDEA XC

Printed on 24/02/2020

Page n. 1/17

Replaced revision:7 (Dated: 07/05/2018)

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 071CXC - 071CXC005A - 071CXC030 - 071CXC030A - 071CXCCAMP - 071CXC200 - 071CXC00500 - 071CXC005 - 071CXC00250 - 071CXC001A - 071CXC001

Product name: IDEA XC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Hydro and oil repellent product with "wet" effect for the treatment of marble, granite, terracotta and stone surfaces in general

1.3. Details of the supplier of the safety data sheet

Name: BELLINZONI S.R.L.
Full address: Via Mezzano 64
District and Country: 28069 Trecate (NO) Italia
Tel. +39 0321 770558 - +39 02 33912133
Fax +39 02-33915224

e-mail address of the competent person

responsible for the Safety Data Sheet: laboratorio@bellinzoni.com
Product distribution by: BELLINZONI S.r.l.

1.4. Emergency telephone number

For urgent inquiries refer to: E.U.: Centro Antiveleni - Ospedale di Niguarda - Milano - Tel. +39 0266101029

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aspiration hazard, category 1

H304

May be fatal if swallowed and enters airways.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

IDEA XC

Hazard pictograms:



Signal words: Danger

Hazard statements:

H304 May be fatal if swallowed and enters airways.
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH210 Safety data sheet available on request.

Precautionary statements:

P301+P310 IF SWALLOWED: immediately call a POISON CENTER / doctor / . . .
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331 Do NOT induce vomiting.
P280 Wear protective gloves / protective clothing / eye protection / face protection.
P332+P313 If skin irritation occurs: Get medical advice / attention.

Contains: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients**3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics		
CAS -	55 ≤ x < 70	Asp. Tox. 1 H304, EUH066
EC 918-481-9		
INDEX -		
Reg. no. 01-2119457273-39		
2-(2-ethoxyethoxy)ethyl acetate		
CAS 112-15-2	4 ≤ x < 5	Eye Irrit. 2 H319
EC 203-940-1		
INDEX -		
Reg. no. 01-2119966911-29		
Ethyl Acetate		

IDEA XCCAS 141-78-6 $2 \leq x < 3$ Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC 205-500-4

INDEX 607-022-00-5

Reg. no. 01-2119475103-46

MethanolCAS 67-56-1 $0 \leq x < 0,1$ Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370

EC 200-659-6

INDEX 603-001-00-X

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.



BELLINZONI S.R.L.

Revision nr. 8

Dated 24/02/2020

Printed on 24/02/2020

Page n. 4/17

Replaced revision:7 (Dated: 07/05/2018)

IDEA XC

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

IDEA XC
Regulatory References:

BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г (4 Септември 2018г)
CZE	Česká Republika	Nařízení vlády č. 246/2018 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
DNK	Danmark	Bekendtgørelse om ændring af bekendtgørelse om grænseværdier for stoffer og materialer1- BEK nr 655 af 31/05/2018
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition,published 2018)
GRC	Ελλάδα	ΕΦΗΜΕΡΙΔΑ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 152 - 21 Αυγούστου 2018
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
NLD	Nederland	Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018, 2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2017/164 in Bijlage XIII
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
ROU	România	HOTĂRÂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
SWE	Sverige	Hygieniska gränsvärden, AFS 2018:1
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2019

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	1200	184			CEFIC-HSPA

2-(2-ethoxyethoxy)ethyl acetate

Predicted no-effect concentration - PNEC

Normal value in fresh water		11	mg/l
Normal value in marine water		0,01	mg/l
Normal value for fresh water sediment		4768	mg/kg
Normal value for marine water sediment		0,04768	mg/kg
Normal value for water, intermittent release		1,1	mg/l
Normal value of STP microorganisms		10	mg/l
Normal value for the terrestrial compartment		448	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0.75 mg/kg bw/d				
Inhalation			VND	2,6 mg/m3			VND	10.45 mg/m3
Skin			VND	0.75 mg/kg bw/d			VND	1.48 mg/kg bw/d

Ethyl Acetate
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	

IDEA XC

		mg/m3	ppm	mg/m3	ppm
TLV	BGR	734	200	1468	400
TLV	CZE	700	194,6	900	250,2
AGW	DEU	730	200	1460	400
MAK	DEU	750	200	1500	400
TLV	DNK	540	150		
VLA	ESP	734	200	1468	400
VLEP	FRA	1400	400		
WEL	GBR	734	200	1468	400
TLV	GRC	734	200	1468	400
VLEP	ITA	734	200	1468	400
TGG	NLD	734		1468	
NDS/NDSch	POL	734		1468	
VLE	PRT	734	200	1468	400
TLV	ROU	400	111	500	139
NGV/KGV	SWE	550	150	1100	300
OEL	EU	734	200	1468	400
TLV-ACGIH		1441	400		

Predicted no-effect concentration - PNEC

Normal value in fresh water		24		mg/l
Normal value in marine water		2		mg/l
Normal value for fresh water sediment		115		mg/kg/dw
Normal value for marine water sediment		0,115		mg/kg/dw
Normal value of STP microorganisms		650		mg/l
Normal value for the terrestrial compartment		0,148		mg/kg/dw

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				4.5 mg/kg bw/d				4.5
Inhalation	734 mg/m3	734 mg/m3	367 mg/m3	367 mg/m3	1468 mg/m3	1468 mg/m3	734 mg/m3	734 mg/m3
Skin				37 mg/kg bw/d				63 mg/kg bw/d

Methanol
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	260	200			SKIN
TLV	CZE	250	188,5	1000	754	SKIN
AGW	DEU	270	200	1080	800	SKIN
MAK	DEU	130	100	260	200	SKIN
TLV	DNK	260	200			SKIN E
VLA	ESP	266	200			SKIN

IDEA XC

VLEP	FRA	260	200	1300	1000	SKIN	11
WEL	GBR	266	200	333	250	SKIN	
TLV	GRC	260	200	325	250		
VLEP	ITA	260	200			SKIN	
TGG	NLD	133				SKIN	
NDS/NDSch	POL	100		300		SKIN	
VLE	PRT	260	200			SKIN	
TLV	ROU	260	200			SKIN	
NGV/KGV	SWE	250	200	350 (C)	250 (C)	SKIN	
OEL	EU	260	200			SKIN	
TLV-ACGIH		262	200	328	250	SKIN	

Predicted no-effect concentration - PNEC							
Normal value in fresh water				20,8	mg/l		
Normal value in marine water				2,08	mg/l		
Normal value for fresh water sediment				77	mg/kg/d		
Normal value for marine water sediment				7,7	mg/kg/d		
Normal value for water, intermittent release				1,54	mg/l		
Normal value of STP microorganisms				100	mg/l		
Normal value for the terrestrial compartment				100	mg/kg/d		

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		4 mg/kg bw/d		4 mg/kg bw/d				
Inhalation	26 mg/m3	26 mg/m3	26 mg/m3	26 mg/m3	130 mg/m3	130 mg/m3	130 mg/m3	130 mg/m3
Skin		4 mg/kg bw/d		4 mg/kg bw/d		20 mg/kg bw/d		20 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

TLV of solvent mixture: 1335 mg/m3

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

IDEA XC

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	liquid
Colour	colourless
Odour	characteristic
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	62 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	0,84
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available

IDEA XC

Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

VOC (Directive 2010/75/EC) : 22,00 % - 198,00 g/litre

VOC (volatile carbon) : 18,63 % - 167,71 g/litre

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

Ethyl Acetate

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Ethyl Acetate

Risk of explosion on contact with: alkaline metals,hydrides,oleum.May react violently with: fluorine,strong oxidising agents,chlorosulphuric acid,potassium tert-butoxide.Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

Ethyl Acetate

Avoid exposure to: light,sources of heat,naked flames.

10.5. Incompatible materials

Ethyl Acetate

Incompatible with: acids,bases,strong oxidants,aluminium,nitrates,chlorosulphuric acid.Incompatible materials: plastic materials.

10.6. Hazardous decomposition products

IDEA XC

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information**11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Methanol

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Methanol

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

2-(2-ethoxyethoxy)ethyl acetate

LD50 (Oral) 3930 mg/kg bw/day ratto

LD50 (Dermal) 15300 mg/kg dw coniglio

Ethyl Acetate

LD50 (Oral) 4934 mg/kg dw ratto OCSE 401

LD50 (Dermal) > 20000 mg/Kg-bw coniglio

LC50 (Inhalation) > 6000 mg/l/6h Ratto

IDEA XC

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

LD50 (Oral) > 5000 mcg/Kg ratto

LD50 (Dermal) > 3160 mg/kg coniglio

LC50 (Inhalation) > 5000 mg/m³ 8h ratto (maschio)

Methanol

LD50 (Oral) 1187 mg/kg bw

LD50 (Dermal) 17100 mg/kg bw

LC50 (Inhalation) 43700 mg/m³

reaction mass of dimethyl adipate, dimethyl glutarate and dimethyl succinate

LD50 (Oral) > 5000 mg/kg dw ratto

LD50 (Dermal) > 2000 mg/kg dw ratto

LC50 (Inhalation) > 11 mg/l/4h ratto

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

IDEA XC

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity**2-(2-ethoxyethoxy)ethyl acetate**

LC50 - for Fish	110 mg/l/96h Pimephales promelas
EC50 - for Crustacea	> 100 mg/l/48h Daphnia magna OCSE 202
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h Pseudokirchneriella subcapitata
Chronic NOEC for Algae / Aquatic Plants	> 100 mg/l/72h Pseudokirchneriella subcapitata OCSE 201

Ethyl Acetate

LC50 - for Fish	230 mg/l/96h Pimephales promelas
EC50 - for Crustacea	165 mg/l/48h Daphnia magna
Chronic NOEC for Crustacea	24 mg/l 21giorni Daphnia pulex
Chronic NOEC for Algae / Aquatic Plants	> 100 mg/l Scenedesmus subspicatus

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish	> 1000 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	> 1000 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	> 1000 mg/l/72h Pseudokirchneriella subcapitata

Methanol

LC50 - for Fish	15,4 mg/l/96h
Chronic NOEC for Fish	446,7 mg/l 28d
Chronic NOEC for Crustacea	208 mg/l 21d

reaction mass of dimethyl adipate, dimethyl glutarate and dimethyl succinate

IDEA XC

LC50 - for Fish	24 mg/l/96h pimephales promelas
EC50 - for Crustacea	150 mg/l/48h daphnia magna
EC50 - for Algae / Aquatic Plants	> 85 mg/l/72h pseudokirchneriella subcapitata

12.2. Persistence and degradability

2-(2-ethoxyethoxy)ethyl acetate

Solubility in water 158,88 g/l

Rapidly degradable

Ethyl Acetate

Solubility in water 86000 mg/l

Rapidly degradable

Hydrocarbons, C10-C13, n-alkanes,
isoalkanes, cyclics, <2% aromatics
Entirely degradable

Methanol

Solubility in water 1000 mg/l

Rapidly degradable

reaction mass of dimethyl adipate, dimethyl
glutarate and dimethyl succinate
Rapidly degradable**12.3. Bioaccumulative potential**

2-(2-ethoxyethoxy)ethyl acetate

Partition coefficient: n-octanol/water -0,133 25°C - pH 8.3

Ethyl Acetate

Partition coefficient: n-octanol/water 0,68

BCF 30

Methanol

Partition coefficient: n-octanol/water -0,77

BCF 0,2

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects



BELLINZONI S.R.L.

Revision nr. 8

Dated 24/02/2020

Printed on 24/02/2020

Page n. 14/17

Replaced revision:7 (Dated: 07/05/2018)

IDEA XC

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable



BELLINZONI S.R.L.

Revision nr. 8

Dated 24/02/2020

Printed on 24/02/2020

Page n. 15/17

Replaced revision:7 (Dated: 07/05/2018)

IDEA XC

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

IDEA XC

A chemical safety assessment has been performed for the following contained substances

2-(2-ethoxyethoxy)ethyl acetate

Ethyl Acetate

Methanol

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Acute Tox. 3	Acute toxicity, category 3
STOT SE 1	Specific target organ toxicity - single exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
Eye Irrit. 2	Eye irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train



BELLINZONI S.R.L.

Revision nr. 8

Dated 24/02/2020

Printed on 24/02/2020

Page n. 17/17

Replaced revision:7 (Dated: 07/05/2018)

IDEA XC

- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

01 / 03 / 05 / 08.