



**BELLINZONI S.R.L.**

Revision nr. 6

Dated 03/03/2020

Printed on 03/03/2020

Page n. 1/16

Replaced revision:5 (Dated: 24/05/2018)

**IDEA DARK**

## Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: **082CDARK - 082CDARK200 - 082CDARK001 - 082CDARK00200 - 082CDARK00250 - 082CDARK005 - 082CDARK025 - 082CDARK00500**  
Product name **IDEA DARK**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Waterproofing and intensifying the color of marble, granite and stone**

#### 1.3. Details of the supplier of the safety data sheet

Name **BELLINZONI S.R.L.**  
Full address **Via Mezzano 64**  
District and Country **28069 Trecate (NO)**  
**Italia**  
**Tel. +39 0321 770558 - +39 02 33912133**  
**Fax +39 02-33915224**

e-mail address of the competent person responsible for the Safety Data Sheet **laboratorio@bellinzoni.com**  
Product distribution by: **BELLINZONI S.r.l.**

#### 1.4. Emergency telephone number

For urgent inquiries refer to **E.U.: Centro Antiveleni - Ospedale di Niguarda - Milano - Tel. +39 0266101029**

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

**IDEA DARK**

Hazard pictograms:



Signal words:

Danger

Hazard statements:

**H226** Flammable liquid and vapour.  
**H304** May be fatal if swallowed and enters airways.  
**H336** May cause drowsiness or dizziness.  
**EUH066** Repeated exposure may cause skin dryness or cracking.  
**EUH210** Safety data sheet available on request.

Precautionary statements:

**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**P261** Avoid breathing dust / fume / gas / mist / vapours / spray.  
**P280** Wear protective gloves/ protective clothing / eye protection / face protection.  
**P301+P310** IF SWALLOWED: immediately call a POISON CENTER / doctor / . . .  
**P331** Do NOT induce vomiting.  
**P501** Dispose of contents / container to . . .

**Contains:** hydrocarbons C9-C11, n-alkanes, isolacans, cyclic, <2% aromatic

**2.3. Other hazards**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**SECTION 3. Composition/information on ingredients****3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>hydrocarbons C9-C11, n-alkanes, isolacans, cyclic, &lt;2% aromatic</b>		
CAS 64742-48-9	$55 \leq x < 70$	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336
EC 919-857-5		
INDEX -		
Reg. no. 01-2119463258-33		
<b>ethyl silicate</b>		
CAS 78-10-4	$0,3 \leq x < 0,4$	Flam. Liq. 3 H226, Acute Tox. 4 H332, Eye Irrit. 2 H319, STOT SE 3 H335
EC 201-083-8		
INDEX 014-005-00-0		

**IDEA DARK****toluene**

CAS 108-88-3

0,2 ≤ x &lt; 0,3

Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336

EC 203-625-9

INDEX 601-021-00-3

Reg. no. 01-2119471310-51

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**SECTION 4. First aid measures****4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures****5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).



**BELLINZONI S.R.L.**

Revision nr. 6

Dated 03/03/2020

Printed on 03/03/2020

Page n. 4/16

Replaced revision:5 (Dated: 24/05/2018)

**IDEA DARK**

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

Regulatory References:

**IDEA DARK**

BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г (4 Септември 2018г)
CZE	Česká Republika	Nařízení vlády č. 246/2018 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
DNK	Danmark	Bekendtgørelse om ændring af bekendtgørelse om grænseværdier for stoffer og materialer1- BEK nr 655 af 31/05/2018
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition,published 2018)
GRC	Ελλάδα	ΕΦΗΜΕΡΙΔΑ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 152 - 21 Αυγούστου 2018
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
NLD	Nederland	Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018, 2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2017/164 in Bijlage XIII
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
ROU	România	HOTĂRÂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
SWE	Sverige	Hygieniska gränsvärden, AFS 2018:1
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2019

**hydrocarbons C9-C11, n-alkanes, isolacans, cyclic, <2% aromatic**
**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH		1200	197			

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				300 mg/kg bw/d				
Inhalation				900 mg/m3				1500 mg/m3
Skin				300 mg/kg bw/d				300 mg/kg bw/d

**ethyl silicate**
**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	44	5			
TLV	CZE	50	5,85	200	23,4	
AGW	DEU	12	1,4	12 (C)	1,4 (C)	
MAK	DEU	86	10	86	10	
TLV	DNK	85	10			
VLEP	FRA	85	10			
WEL	GBR	44	5			
TLV	GRC	44	5			
VLEP	ITA	44	5			

**IDEA DARK**

TGG	NLD	44	
NDS/NDSch	POL	44	
VLE	PRT	44	5
TLV	ROU	44	5
OEL	EU	44	5
TLV-ACGIH		85	10

**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,192	mg/l
Normal value in marine water	0,0192	mg/l
Normal value for fresh water sediment	0,18	mg/kg
Normal value for marine water sediment	0,018	mg/kg
Normal value for water, intermittent release	10	mg/l
Normal value of STP microorganisms	4000	mg/l
Normal value for the terrestrial compartment	0,05	mg/kg

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	25 mg/m3	25 mg/m3	25 mg/m3	25 mg/m3	85 mg/m3	85 mg/m3	85 mg/m3	85 mg/m3
Skin		8,4 mg/kg/d		8,4 mg/kg/d				

**toluene**
**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	192	50	384	100	SKIN
TLV	CZE	200	53,2	500	133	SKIN
AGW	DEU	190	50	760	200	SKIN
MAK	DEU	190	50	760	200	SKIN
TLV	DNK	94	25			SKIN E
VLA	ESP	192	50	384	100	SKIN
VLEP	FRA	76,8	20	384	100	SKIN
WEL	GBR	191	50	384	100	SKIN
TLV	GRC	192	50	384	100	
VLEP	ITA	192	50			SKIN
TGG	NLD	150		384		
NDS/NDSch	POL	100		200		SKIN
VLE	PRT	192	50	384	100	SKIN
TLV	ROU	192	50	384	100	SKIN
NGV/KGV	SWE	192	50	384	100	SKIN
OEL	EU	192	50	384	100	SKIN
TLV-ACGIH		75,4	20			

**Predicted no-effect concentration - PNEC**

**IDEA DARK**

Normal value in fresh water	0,68	mg/l
Normal value in marine water	0,68	mg/l
Normal value for fresh water sediment	16,39	mg/kg/d
Normal value for marine water sediment	16,39	mg/kg/d
Normal value for water, intermittent release	0,68	mg/l
Normal value of STP microorganisms	13,61	mg/l
Normal value for the terrestrial compartment	2,89	mg/kg

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				8,16 mg/kg bw/d				
Inhalation				56,5 mg/m3	384 mg/m3			192 mg/m3
Skin				226 mg/kg bw/d				384 mg/kg bw/d

## Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

TLV of solvent mixture: 75 mg/m3

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

**HAND PROTECTION**

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of

**IDEA DARK**

various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**SECTION 9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Appearance	liquid
Colour	transparent
Odour	characteristic
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	> 36 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	0,86 g/l
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

**9.2. Other information**

VOC (Directive 2010/75/EC) :	65,24 % - 554,54 g/litre
VOC (volatile carbon) :	55,26 % - 469,68 g/litre

**IDEA DARK****SECTION 10. Stability and reactivity****10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

toluene

Avoid exposure to: light.

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions**

The vapours may also form explosive mixtures with the air.

toluene

Risk of explosion on contact with: fuming sulphuric acid, nitric acid, silver perchlorate, nitrogen dioxide, non-metal halogenates, acetic acid, organic nitrocompounds. May form explosive mixtures with: air. May react dangerously with: strong oxidising agents, strong acids, sulphur.

**10.4. Conditions to avoid**

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

**10.5. Incompatible materials**

Information not available

**10.6. Hazardous decomposition products**

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

**SECTION 11. Toxicological information****11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

toluene

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**IDEA DARK**

toluene

Interactive effects

toluene

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:  
Not classified (no significant component)  
LD50 (Oral) of the mixture:  
Not classified (no significant component)  
LD50 (Dermal) of the mixture:  
Not classified (no significant component)

toluene

LD50 (Oral) 5580 mg/kg Rat

LD50 (Dermal) 12124 mg/kg Rabbit

LC50 (Inhalation) 25,7 mg/l/4h Rat

hydrocarbons C9-C11, n-alkanes, isolacans, cyclic, <2% aromatic

LD50 (Oral) > 5000 mg/kg Rat, m/f

LD50 (Dermal) > 3160 mg/kg Rabbit, m/f

LC50 (Inhalation) > 4951 mg/m3 Rat

ethyl silicate

LD50 (Oral) > 10 mg/kg/4h rat

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

**IDEA DARK**RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

toluene

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

**SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

**12.1. Toxicity**

toluene

LC50 - for Fish 5,5 mg/l/96h

EC50 - for Algae / Aquatic Plants 3,78 mg/l/72h

hydrocarbons C9-C11, n-alkanes, isolacans,  
cyclic, <2% aromatic

LC50 - for Fish > 1000 mg/l/96h oncorhynchus mykiss

EC50 - for Crustacea > 1000 mg/l/48h daphnia magna

**IDEA DARK**

EC50 - for Algae / Aquatic Plants	> 1000 mg/l/72h pseudokirchneriella subcapitata
ethyl silicate	
LC50 - for Fish	245 mg/l/96h danio rerio
EC50 - for Crustacea	> 75 mg/l/48h daphnia magna
EC50 - for Algae / Aquatic Plants	> 22 mg/l/72h pseudokirchneriella subcapitata

**12.2. Persistence and degradability**

toluene	
Solubility in water	100 - 1000 mg/l
Rapidly degradable	

hydrocarbons C9-C11, n-alkanes, isolacans,  
cyclic, <2% aromatic  
Rapidly degradable

ethyl silicate	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

**12.3. Bioaccumulative potential**

toluene	
Partition coefficient: n-octanol/water	2,73
BCF	90

hydrocarbons C9-C11, n-alkanes, isolacans,  
cyclic, <2% aromatic  
Partition coefficient: n-octanol/water

5,85

ethyl silicate	
Partition coefficient: n-octanol/water	3,18
BCF	3,16

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Other adverse effects**

Information not available

**IDEA DARK****SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information****14.1. UN number**

ADR / RID, IMDG, 1263  
IATA:

**14.2. UN proper shipping name**

ADR / RID: PAINT or PAINT RELATED MATERIAL  
IMDG: PAINT or PAINT RELATED MATERIAL  
IATA: PAINT or PAINT RELATED MATERIAL

**14.3. Transport hazard class(es)**

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3

**14.4. Packing group**

ADR / RID, IMDG, III  
IATA:

**14.5. Environmental hazards**

ADR / RID: NO  
IMDG: NO  
IATA: NO

**14.6. Special precautions for user**

ADR / RID: HIN - Kemler: 30 Limited Tunnel



IDEA DARK

IMDG:	Special Provision: -	Quantities: 5 L	restriction code: (D/E)
	EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Pass.:	Maximum quantity: 60 L	Packaging instructions: 355
	Special Instructions:	A3, A72, A192	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point 3 - 40

Contained substance

Point 48 toluene Reg. no.: 01-2119471310-51

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

**IDEA DARK**

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Repr. 2</b>	Reproductive toxicity, category 2
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.
<b>H361d</b>	Suspected of damaging the unborn child.
<b>H332</b>	Harmful if inhaled.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.
<b>EUH210</b>	Safety data sheet available on request.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods

**IDEA DARK**

- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
  16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

**Changes to previous review:**

The following sections were modified:

08 / 09.