

# BELLINZONI®

## Technical Bulletin

### "GREZZO" PROTECTIVE ENHANCER FOR ROUGH SURFACES

Stone deep enhancer agent and protective

Revised 05-2007 RV/ARB

#### Description:

Deep color enhancing and protective agent, used for intensely increase color of material. It also raises resistance against penetration of water and oils, on surfaces and handmade objects with rough finish. It lets the stone breath, it penetrates deeply, enhancing the colour of the stone and gives an attractive and deep wet look; it does not make any film.

#### Technical Characteristics:

Appearance	liquid
Color	Yellow transparent
Odor	Characteristic of solvent
Specific gravity at 20°C (68°F)	1,30 ± 0,02
Hydro-solubility	Not soluble
pH	n.a.
Superficial drying time at 20°C (68°F)	30 – 60 minutes*
Complete drying time at 20°C (68°F)	4 hours*

\*approximate values, can change depending on nature of material and ambient conditions

#### Instruction for Use:

Surface must be clean and dry; stains, mildew, crusting must be scraped off otherwise they will be harder to remove after protection. Application can be done by brush, by roller or appropriate tool. It is suggested, when possible, to apply the product by brush because it allow the product to penetrate well into the stone. Application of GREZZO by brush, making pressure, will facilitate penetration into frames and cavities. After 30 minutes rub with a clean cloth to remove excess of product.

#### Suggestion for Use:

- On very absorbent material, or to further enhance color of treated material, it is possible to make a second cross-handed application after three hours from the first.
- Do not dilute the product with any solvent or water, formulation is ready for use
- Material, before treatment, has to be completely dry.
- Once the material has been treated it is necessary to wait 24 hours for complete polymerization.
- In case of treatment of statues, decorations etc., pay attention to treat well cavities and corners.
- Read carefully recommendations printed on the tin before use.
- Make always a test before effective application.
- For internal use.

#### Application on surfaces:

Marble, granite, calcareous stones with flamed, semi-polished, lapped or rough finish.

All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure.



# BELLINZONI®

## Technical Bulletin

### "GREZZO" PROTECTIVE ENHANCER FOR ROUGH SURFACES

Stone deep enhancer agent and protective

Revised 05-2007 RV/ARB

#### Safety procedures:

As far as the proper working procedures is concerned, we recommend to consult [Material Safety Data Sheets](#) issued according to E.U. rules and to follow your national laws concerning safety in the working place.

#### Coverage:

With 1 liter (1,05 quart) of product, it is possible to treat up to 10 sqm (110 sq.ft.), depending on material finish and porosity.

#### Packing:

Carton: 12 tins of 1 litre (1,05 quart), 3 tins of 5 litres (1,32 gal) , 1 drum of 30 litres (7,93 gal)

The composition of the tins is Steel (ACC). After use, comply with the local and national regulations currently in force regarding recycling.

Our packing is conformed as per U.N. rules for inland transport (A.D.R.) and by sea (I.M.O.) for transportation via air refer to updated rules (I.A.T.A.). For further information regarding transport please check MSDS.

#### Harmonized Custom Tariff:

3910.0000

All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure.

