

REG NO :2002/028469/23 VAT NO : 4120207339

P.O Box 406 • Milnerton • 7435

MATERIAL SAFETY DATA SHEET Date issued: 03/2018

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Name Tool-Co Lithium Densifier

1.2 Relevant identified uses of the substance or mixture and used advised against

Identified use(s) General purpose industrial chemical for use in a wide range of applica-

tions.

Binding agent; Corrosion inhibitor; Dust binding agent; Flame retardant or fire preventing agent; Flotation agent; Stabiliser; Waterproof seal;

Surface crack repairs; Viscosity control agent

Uses advised against None known.

Company Details Name: MACTOOL Diamond & Construction Products

Address: Unit 6 Pennisi Park, No.3 Jig Ave, Montague Gardens

In case of an emergency contact your local MACTOOL Branch. (Contact Details On Footer)

2. Composition / Information on ingredients

Regulation (EC) No. 1272/2008 (CLP)

			EINECS No. / REACH Registra-	Hazard symbol(s) and hazard state-
Ingredient(s)	%W/W	CAS No.	tion	ment(s)
Silicic acid, Li Salt (1.6 <mr<=2.6)< td=""><td>35-55</td><td>1344-09-8</td><td>215-687-4</td><td>H315 : Skin Irrit. 2 ; H318 : Eye Dam. 1 ; H335 : STOT SE 3 ;</td></mr<=2.6)<>	35-55	1344-09-8	215-687-4	H315 : Skin Irrit. 2 ; H318 : Eye Dam. 1 ; H335 : STOT SE 3 ;
Water	46-65	7732-18-5	231-791-2	

The classification of the ingredient silicic acid, Li Salt is based on the powder form. For full text of R/H phrases see section 16.

JOHANNESBURG



3. Hazardous Identification

3.1 Classification of the substance or mixture

GHS Classification H318: Serious eye damage/irritation Category 1

H315: Skin corrosion/irritation Category 2

Hazards summary Alkaline.

Risk of serious damage to the eyes.

Irritating to skin.

2.2. Label elements

Hazard Pictogram(s)



Signal word(s) Danger

Hazard statement(s) H318 Causes serious eye damage.

H315: Causes skin irritation

Precautionary statement(s) P262: Do not get in eyes, on skin, or on clothing

P280: Wear protective gloves/protective clothing/eye protection/face

protection.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all

contaminated clothing. Rinse skin with water/shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

3.3 Other hazards Not classified as PBT or vPvB.



REG NO :2002/028469/23 VAT NO : 4120207339

P.O Box 406 • Milnerton • 7435

4. First Aid Measures

4.1 Description of first aid measures

<u>Inhalation</u> Remove patient from exposure, keep warm and at rest. Obtain medical

attention.

Skin Contact Wash affected skin with plenty of water. If symptoms develop, obtain

medical attention.

Eye Contact Irrigate with eyewash solution or clean water, holding the eyelids apart,

for at least 15 minutes. Obtain immediate medical attention.

<u>Ingestion</u> Do not induce vomiting. Wash out mouth with water and give 200-300ml

(half a pint) of water to drink. Obtain medical attention

4.2 Most important symptoms and effects, both acute and delayed

Alkaline.

Risk of serious damage to eyes.

Irritating to skin.

The toxicity of The Product is dependent on the silica to alkali ratio and

on the pH

4.3 Indication of any Immediate medical attention and special treatment needed Obtain immediate medical attention

5. Fire Fighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media Unsuitable Extinguishing Media

Compatible with all standard firefighting techniques.

None known.

5.2 Special hazards arising from

the substance or mixture

Not applicable. Aqueous solution. Non-combustible.

5.3 Advice for fire-fighters None.

CAPE TOWN

Unit 6 • Pennisi Park Jig Avenue • Montague Gardens

T. +27 21 552 8566 F. +27 21 552 8575 E. sales@mactool.co.za JOHANNESBURG

Unit 4 • Hughes Industrial Park
Cnr. Oscar & Romeo Roads • Hughes • Boksburg

T. +27 11 823 1077 F. +27 11 823 1065 E. salesjhb@mactool.co.za DURBAN

Unit 1A 44 Hillclimb Road • Westmead

T. +27 31 350 4004 F. +27 31 350 4005 E. saleskzn@mactool.co.za



6. Accidental Release Measures

6.1 Personal precautions, Protective equipment and emergency procedures Wear suitable protective clothing. Wear eye/face protection.

See Section: 8.2

6.2 Environmental precautions

Do not allow to enter drains, sewers or watercourses. Advise Authorities if spillage has entered water course or sewers or has contaminated soil or

vegetation.

6.3 Methods and materials for containment and cleaning up

Caution – spillages may be slippery. Contain spillages with sand, earth or any suitable adsorbent material. Transfer to a container for disposal or

recovery.

6.4 Reference to other sections

See Also Section 8.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing.

Avoid generation of mist. Provide adequate ventilation.

Emergency shower and eye wash facilities should be readily available.

See Also Section 8

7.2 Conditions for safe storage, including any incompatibilities

Keep at a temperature not exceeding (°C): 50

Do not allow material to freeze. Provide an adequate bund wall. Unsuitable containers: Aluminium

See Also Section 10.

7.3 Specific end use(s)

Not known.

CAPE TOWN



8. Exposure Controls/Personal Protection

8.1 Control parameters

SUBSTANCE.	Occupational Exposure Limits	
Silicic acid, Li Salt	No Occupational Exposure Limit assigned.	
	An exposure limit of 2 mg/m3 (15 min TWA) is recommended by	
	analogy with sodium hydroxide (UK EH40).	

	Oral / mg/kg	Inhalation	Dermal / mg/kg
Derived No Effect Level (DNEL)	bw/d	/ mg/m³	bw/d
Workers - Acute - Systematic effects	-	-	-
Workers - Acute - Local effects	-	-	-
Workers - Long Term - Systematic effects	-	5.61	1.59
Workers - Long Term - Local effects	-	-	-
Consumers - Acute - Systematic effects	-	-	-
Consumers - Acute - Local effects	-	-	-
Consumers - Long Term - Systematic effects	0.80	1.38	0.80
Consumers - Long Term - Local effects	_	-	-

Risk management measures (RMMs) for identified uses must be implemented as described in this SDS.

	Predicated No Effect Concentration
PNEC Water (fresh)	7.5 mg/l
PNEC Water (marine)	1 mg/l
PNEC Water (intermittent)	7.5 mg/l
PNEC Sediment	Not available
PNEC Soil	Not available
PNEC Sewage treatment plant	348 mg/l
PNEC Secondary Poisoning (oral)	Not available





8.2 Exposure controls Wear protective equipment to comply with good occupational hygiene

practice. Do not eat, drink or smoke at the work place.

8.2.1 Appropriate Engineering methods to prevent or control exposure are preferred. **Engineering Controls**

Methods include process or personnel enclosure, mechanical ventilation

(dilution and local exhaust), and control of process conditions.

8.2.2 Personal Protection

Respiratory protection Respiratory protection not normally required. Advice on respiratory

protective equipment is given in the HSE (Health Safety Executive) publi-

cation HS(G)53.

Eye/face protection Chemical goggles (EN 166)

Wear suitable protective clothing and gloves. Skin protection

Plastic or rubber gloves. For example EN374-3, level 6

breakthrough time (>480min).

Wear suitable overalls. For example EN ISO 13982 (dust), EN 14605 (liquid

splashes).

8.2.3 Environmental Exposure The primary hazard of is the alkalinity. Avoid release to the environment



REG NO :2002/028469/23 VAT NO : 4120207339

P.O Box 406 · Milnerton · 7435

9. Physical & Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance Liquid. Almost colourless.

Odour Odourless.
Odour Threshold (ppm) Not applicable.
pH (Value) Strongly alkaline.

Freezing Point (°C) No data

Melting Point (°C) Not applicable.

Boiling Point (°C) 100

Flash Point (°C) [Closed cup]

Evaporation rate

Flammability (solid, gas)

Explosive Limit Ranges

Vapour Pressure (mm Hg)

Not applicable.

Not applicable.

Not applicable.

Vapour Density (Air=1) No data.

Density (g/ml) 1.4 - 1.6 (typically)

Solubility (Water) Soluble.
Solubility (Other) No data.
Partition Coefficient No data.

Auto Ignition Point (°C) Not applicable. Decomposition Temperature (°C) Not applicable.

Viscosity (mPa. s) No data.

Explosive properties Not applicable. Oxidising Properties Not applicable.

9.2 Other Information No data.

CAPE TOWN

Unit 6 • Pennisi Park Jig Avenue • Montague Gardens

T. +27 21 552 8566 F. +27 21 552 8575 E. sales@mactool.co.za **JOHANNESBURG**

Unit 4 • Hughes Industrial Park
Cnr. Oscar & Romeo Roads • Hughes • Boksburg

T. +27 11 823 1077 F. +27 11 823 1065 E. salesjhb@mactool.co.za DURBAN

Unit 1A 44 Hillclimb Road • Westmead

T. +27 31 350 4004 F. +27 31 350 4005 E. saleskzn@mactool.co.za



10. Stability and Reactivity

10.1 Reactivity See section: 10.3

10.2 Chemical stability Stable.

10.3 Possibility of hazardous

Reactions When arc welding vessels containing aqueous solutions of this material,

take care to control any explosion risk from hydrogen evolved by electrolysis. Aqueous solutions will react with aluminum, zinc, tin and their alloys evolving hydrogen gas which can form an explosive mixture with air. Can react violently if in contact with acids. Can react with sugar residues to

form carbon monoxide.

10.4 Conditions to avoid See Section: 10.3 **10.5 Incompatible materials** See Section: 10.3

11. Toxicological Information:

11.1 Information on toxicological effects

Acute toxicity

Ingestion All symptoms of acute toxicity are due to high alkalinity. Material will

cause irritation. Oral LD50 (rat) 3400 mg/kg bw

Inhalation Mist is irritant to the respiratory tract. All symptoms of acute toxicity are

due to high alkalinity. Inhalation LC50 (rat) >2.06 g/m3

Skin Contact Material will cause irritation. Dermal LD50 (rat) >5000 mg/kg bw

Eye Contact Material will cause severe irritation. Risk of serious damage to eyes.

Skin corrosion/ Irritation Irritating to skin.

Serious Eye damage/irritation Irritating to eyes. Risk of serious damage to eyes.

Sensitisation Not sensitising.

Mutagenicity No evidence of genotoxicity. In vitro/in vivo negative.

Carcinogenicity No structural alerts.

Reproduce toxicityNo evidence of reproductive toxicity or developmental toxicity.

STOT – single exposure Not classified.

STOT – repeated exposure Not classified. NOAEL oral (rat) >159 mg/kg bw/d

Aspiration hazard Not classified.

CAPE TOWN

T. +27 21 552 8566 F. +27 21 552 8575 E. sales@mactool.co.za

JOHANNESBURG

Unit 4 • Hughes Industrial Park Cnr. Oscar & Romeo Roads • Hughes • Boksburg

> T. +27 11 823 1077 F. +27 11 823 1065 E. salesjhb@mactool.co.za

DURBAN

Unit 1A 44 Hillclimb Road • Westmead

T. +27 31 350 4004 F. +27 31 350 4005 E. saleskzn@mactool.co.za



12. Ecological Information

12.1 Toxicity Fish (Brachydanio rerio) LC50 (96 hour) 1108 mg/l

Aquatic invertebrates: (Daphnia magna) EC50 (48 hour) 1700 mg/l

Inorganic. Soluble silicates, upon dilution, rapidly depolymerise 12.2 Persistence and degradability

into molecular species indistinguishable from natural dissolved silica.

12.3 Bioaccumulative potential

Inorganic. The substance has no potential for bioaccumulation. Not applicable.

12.4 Mobility in soil

12.5 Results of PBT and vPvB

Not classified as PBT or vPvB

assessment

12.6 Other adverse effects The alkalinity of this material will have a local effect on ecosystems sensi-

tive to changes in pH

13. Disposal Considerations

13.1 Waste treatment methods

Discharge of this product to sewage treatment works is dependent on local regulation with regard to pH controls. Dispose of this material and its container to hazardous or special waste collection

Disposal should be in accordance with local, state or national

legislation.

14. Transport Information

Not classified according to the United Nations 'Recommendation on the Transport of Dangerous Goods'.

14.1 UN Number Not applicable. 14.2 Proper Shipping Name Not applicable.

14.3 Transport hazard class(es) Not applicable.

14.4 Packing group Not applicable.

14.5 Environmental hazards Not classified as a Marine Pollutant.

T. +27 21 552 8566 F. +27 21 552 8575

E. sales@mactool.co.za

JOHANNESBURG



15. Regulatory Information:

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

TSCA Inventory Status: Reported/Included.
AICS Inventory Status: Reported/Included.
DSL/NDSL Inventory Status: Reported/Included.

German Water Hazard Classification VwVwS: Product ID number 1314, WGK class 1 (low hazard to water).

16. Other Information:

Data referenced in this eSDS is from company-owned information and from data legitimately accessed by MACTOOL through membership of Industry Consortia or other agreements. This includes data relating to toxicology, ecotoxicology, DNELs, PNECs and other information in this eSDS and its annex.

This SDS was last reviewed: 05/2016

The following sections contain revisions or new statements: All sections.

GLOSSARY

H315: Causes skin irritation.

H318: Causes serious eye damage.H335: May cause respiratory irritation.

STOT SE 3: Specific target organ toxicity – single exposure Category 3

DNEL: Derived No effect Level

PNEC: Predicted No Effect Concentration
PBT: Persistent, Bioaccumulative and Toxic

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. MACTOOL gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. MACTOOL accepts no liability for loss or damage and makes no warranty, expressed or implied, concerning the product or the merchantability or fitness thereof for any purpose or concerning the accuracy of any information provided by MACTOOL, except that the product shall conform to contracted specifications. Freedom under Patents, Copyright and Designs cannot be assumed.