



34 B

700364

Key features

Needles ø 3 mm	28 pcs. pointed
Air consumption	125 L/Min, 4.4 cfm
Max. permitted air pressure	7 bar, 100 psi
Vibration value on handle	17.10 m/s ²
Sound pressure level	≤ 100.7 db(A)
Acoustic power level	≤ 110.0 db(A)

Field of application

The unit is intended for machining the surfaces of metal, concrete and stone for the purposes of cleaning, derusting, roughening, descaling, clearing, smoothing and bush-hammering.

Physical parameters

Weight	3.0 kg / 6.6 lbs
Connection thread	G 3/8"

Packaging



Case size 475×360×110 mm / 18.7×14.1×4.3"

One case contains

34 B needle scalar
Hose connection G3/8 × 10 mm
Auxiliary handle
VAC Connector
Tube of grease
Operating manual

Recommended lubricants

BP	Energol RD-E46
Mobil	Almo Oil 325
Shell	Torcula 100
DEA	Arkas 32
Texaco	Aries 32
Esso	Arox EP 46 or EP 100

Spare parts

Set needles compl.	∅ 2 mm. blunt	∅ 3 mm. blunt	∅ 3 mm. pointed	∅ 4 mm. blunt	∅ 4 mm. pointed
Article code	700349	700350	700352	700351	700353

